



ADAPTER**1BJ**

BSP MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL / JIC MALE 74° CONE

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	L	S1	
1BJ-02-04Z	G1/8"X28	7/16"X20			10	14	30	14	
1BJ-02-05Z	G1/8"X28	1/2"X20			10	14	30	14	
1BJ-02-06Z	G1/8"X28	9/16"X18			10	14.1	30	17	
1BJ-04Z	G1/4"X19	7/16"X20			12	14	32	19	
1BJ-04-05Z	G1/4"X19	1/2"X20			12	14	32	19	
1BJ-04-06Z	G1/4"X19	9/16"X18			12	14.1	32	19	
1BJ-04-08Z	G1/4"X19	3/4"X16			12	16.7	36.5	22	
1BJ-04-10Z	G1/4"X19	7/8"X14			12	19.3	39	24	
1BJ-06Z	G3/8"X19	9/16"X18			13.5	14.1	35.5	22	
1BJ-06-04Z	G3/8"X19	7/16"X20			13.5	14	35.5	22	
1BJ-06-05Z	G3/8"X19	1/2"X20			13.5	14	35.5	22	
1BJ-06-08Z	G3/8"X19	3/4"X16			13.5	16.7	38.5	22	
1BJ-06-10Z	G3/8"X19	7/8"X14			13.5	19.3	41	24	
1BJ-06-12Z	G3/8"X19	1.1/16"X12			13.5	21.9	45	30	
1BJ-08Z	G1/2"X14	3/4"X16			16	16.7	43	27	
1BJ-08-04Z	G1/2"X14	7/16"X20			16	14	40	27	
1BJ-08-05Z	G1/2"X14	1/2"X20			16	14	40	27	
1BJ-08-06Z	G1/2"X14	9/16"X18			16	14.1	40	27	
1BJ-08-10Z	G1/2"X14	7/8"X14			16	19.3	45.5	27	
1BJ-08-12Z	G1/2"X14	1.1/16"X12			16	21.9	48	30	
1BJ-08-14Z	G1/2"X14	1.3/16"X12			16	22.6	49.5	32	
1BJ-08-16Z	G1/2"X14	1.5/16"X12			16	23.1	50	36	
1BJ-10Z	G5/8"X14	7/8"X14			17.5	19.3	47	30	
1BJ-10-08Z	G5/8"X14	3/4"X16			17.5	16.7	44	30	
1BJ-10-12Z	G5/8"X14	1.1/16"X12			17.5	21.9	49.5	30	
1BJ-10-16Z	G5/8"X14	1.5/16"X12			17.5	23.1	51.5	36	
1BJ-12Z	G3/4"X14	1.1/16"X12			18.5	21.9	51.5	32	
1BJ-12-06Z	G3/4"X14	9/16"X18			18.5	14.1	43.5	32	
1BJ-12-08Z	G3/4"X14	3/4"X16			18.5	16.7	46.5	32	
1BJ-12-10Z	G3/4"X14	7/8"X14			18.5	19.3	49	32	
1BJ-12-14Z	G3/4"X14	1.3/16"X12			18.5	22.6	52	32	
1BJ-12-16Z	G3/4"X14	1.5/16"X12			18.5	23.1	52.5	34	
1BJ-12-20Z	G3/4"X14	1.5/8"X12			18.5	24.3	55.5	46	
1BJ-16Z	G1"X11	1.5/16"X12			20.5	23.1	56	41	
1BJ-16-08Z	G1"X11	3/4"X16			20.5	16.7	50	41	
1BJ-16-10Z	G1"X11	7/8"X14			20.5	19.3	53	41	
1BJ-16-12Z	G1"X11	1.1/16"X12			20.5	21.9	55.5	41	
1BJ-16-14Z	G1"X11	1.3/16"X12			20.5	22.6	56	41	
1BJ-16-20Z	G1"X11	1.5/8"X12			20.5	24.3	58	46	
1BJ-20Z	G1.1/4"X11	1.5/8"X12			20.5	24.3	62	50	



1BJ

BSP MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL / JIC MALE 74° CONE

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	L	S1	
1BJ-20-12Z	G1.1/4"X11	1.1/16"X12			20.5	21.9	57.5	50	
1BJ-20-16Z	G1.1/4"X11	1.5/16"X12			20.5	23.1	60.5	50	
1BJ-20-24Z	G1.1/4"X11	1.7/8"X12			20.5	27.5	63	50	
1BJ-24-16Z	G1.1/2"X11	1.5/16"X12			23	23.1	61	55	
1BJ-24-20Z	G1.1/2"X11	1.5/8"X12			23	24.3	62.5	55	
1BJ-24Z	G1.1/2"X11	1.7/8"X12			23	27.5	67.5	55	
1BJ-24-32Z	G1.1/2"X11	2.1/2"X12			23	33.9	74	65	
1BJ-32Z	G2"X11	2.1/2"X12			25.5	33.9	77.5	70	
1BJ-32-24Z	G2"X11	1.7/8"X12			25.5	27.5	70	70	

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	1BJ-08Z
304 stainless steel	SR	1BJ-08SR
316L stainless steel	SV	1BJ-08SV
316Ti stainless steel	SY	1BJ-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1BJ-08Z	96	360
Durakote plating	ZD	1BJ-08ZD	360	720
Zinc-nickel plating	ZN	1BJ-08ZN	1000	-