


ADAPTER




1BN

BSP MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL / NPT MALE

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	L	S1	
1BN-02Z	G1/8"X28	Z1/8"X27			10	10.5	26	14	
1BN-02-04Z	G1/8"X28	Z1/4"X18			10	15	31	17	
1BN-04Z	G1/4"X19	Z1/4"X18			12	15	33	19	
1BN-04-02Z	G1/4"X19	Z1/8"X27			12	10.5	28	19	
1BN-04-06Z	G1/4"X19	Z3/8"X18			12	16	34	19	
1BN-04-08Z	G1/4"X19	Z1/2"X14			12	19.5	39.5	22	
1BN-06Z	G3/8"X19	Z3/8"X18			13.5	16	37.5	22	
1BN-06-04Z	G3/8"X19	Z1/4"X18			13.5	15	36.5	22	
1BN-06-08Z	G3/8"X19	Z1/2"X14			13.5	19.5	41	22	
1BN-06-12Z	G3/8"X19	Z3/4"X14			13.5	19.5	43	30	
1BN-08Z	G1/2"X14	Z1/2"X14			16	19.5	45.5	27	
1BN-08-06Z	G1/2"X14	Z3/8"X18			16	15	42	27	
1BN-08-12Z	G1/2"X14	Z3/4"X14			16	19.5	45.5	30	
1BN-08-16Z	G1/2"X14	Z1"X11.5			16	25.5	52.5	36	
1BN-10-08Z	G5/8"X14	Z1/2"X14			17.5	19.5	47	30	
1BN-10-12Z	G5/8"X14	Z3/4"X14			17.5	19.5	47	30	
1BN-12Z	G3/4"X14	Z3/4"X14			18.5	19.8	49	32	
1BN-12-06Z	G3/4"X14	Z3/8"X18			18.5	16	45.5	32	
1BN-12-08Z	G3/4"X14	Z1/2"X14			18.5	19.8	49	32	
1BN-12-16Z	G3/4"X14	Z1"X11.5			18.5	24.6	53.4	36	
1BN-16Z	G1"X11	Z1"X11.5			20.5	24.6	59	41	
1BN-16-12Z	G1"X11	Z3/4"X14			20.5	19.8	53	41	
1BN-16-20Z	G1"X11	Z1.1/4"X11.5			20.5	26.5	60	46	
1BN-20Z	G1.1/4"X11	Z1.1/4"X11.5			20.5	25.4	62	50	
1BN-20-16Z	G1.1/4"X11	Z1"X11.5			20.5	25.5	61	50	
1BN-20-24Z	G1.1/4"X11	Z1.1/2"X11.5			20.5	27.5	63	50	
1BN-24Z	G1.1/2"X11	Z1.1/2"X11.5			23	27.5	65.5	55	
1BN-24-20Z	G1.1/2"X11	Z1.1/4"X11.5			23	26.5	64.5	55	
1BN-24-32Z	G1.1/2"X11	Z2"X11.5			23	27.5	67.5	65	
1BN-32Z	G2"X11	Z2"X11.5			25.5	26.9	70	70	
1BN-32-20Z	G2"X11	Z1.1/4"X11.5			25.5	26.5	69	70	
1BN-32-24Z	G2"X11	Z1.1/2"X11.5			25.5	27.5	70	70	

ADAPTER



1BN

BSP MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL / NPT MALE

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	L	S1	

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	1BN-08Z
304 stainless steel	SR	1BN-08SR
316L stainless steel	SV	1BN-08SV
316Ti stainless steel	SY	1BN-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1BN-08Z	96	360
Durakote plating	ZD	1BN-08ZD	360	720
Zinc-nickel plating	ZN	1BN-08ZN	1000	-