


ADAPTER**2TB-SP**

BSPT MALE / BSP FEMALE 60° CONE

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	L	S1	S2
2TB-02SPZ	R1/8"X28	G1/8"X28			10	5.5	25	12	14
2TB-04SPZ	R1/4"X19	G1/4"X19			14.5	5.5	31.5	17	19
2TB-06SPZ	R3/8"X19	G3/8"X19			15	6.3	33	19	22
2TB-06-04SPZ	R3/8"X19	G1/4"X19			15	5.5	32	19	19
2TB-06-08SPZ	R3/8"X19	G1/2"X14			15	7.5	35	19	27
2TB-08SPZ	R1/2"X14	G1/2"X14			20	7.5	42	22	27
2TB-08-06SPZ	R1/2"X14	G3/8"X19			20	6.3	40	22	22
2TB-08-12SPZ	R1/2"X14	G3/4"X14			20	10.9	45	27	32
2TB-12SPZ	R3/4"X14	G3/4"X14			20	10.9	45	30	32
2TB-12-08SPZ	R3/4"X14	G1/2"X14			20	7.5	44	30	27
2TB-12-16SPZ	R3/4"X14	G1"X11			20	11.7	47	32	41
2TB-16SPZ	R1"X11	G1"X11			25.5	11.7	52.5	36	41
2TB-16-12SPZ	R1"X11	G3/4"X14			25.5	10.9	51.5	36	32
2TB-20-16SPZ	R1.1/4"X11	G1"X11			26.5	11.7	55.5	46	41
2TB-20SPZ	R1.1/4"X11	G1.1/4"X11			26.5	10.1	59	46	50
2TB-24SPZ	R1.1/2"X11	G1.1/2"X11			26.5	12.5	61.5	50	55
2TB-32SPZ	R2"X11	G2"X11			30	16.1	67	65	70

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2TB-08SPZ
304 stainless steel	SR	2TB-08SPSR
316L stainless steel	SV	2TB-08SPSV
316Ti stainless steel	SY	2TB-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2TB-08SPZ	96	360
Durakote plating	ZD	2TB-08SPZD	360	720
Zinc-nickel plating	ZN	2TB-08SPZN	1000	-