



4B

BSP MALE DOUBLE USE FOR 60° CONE SEAT OR
BONDED SEAL PLUG

PART NO.	THREAD				DIMENSIONS				
	E				A	L	S1		
4B-02Z	G1/8"X28				10	16	14		
4B-04Z	G1/4"X19				12	18	19		
4B-06Z	G3/8"X19				13.5	21.5	22		
4B-08Z	G1/2"X14				16	26	27		
4B-10Z	G5/8"X14				17.5	27.5	30		
4B-12Z	G3/4"X14				18.5	29.5	32		
4B-16Z	G1"X11				20.5	34	41		
4B-20Z	G1.1/4"X11				20.5	37.5	50		
4B-24Z	G1.1/2"X11				23	40	55		
4B-32Z	G2"X11				25.5	43.5	70		

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	4B-08Z
304 stainless steel	SR	4B-08SR
316L stainless steel	SV	4B-08SV
316Ti stainless steel	SY	4B-08SY

2. Plating options and performance for carbon steel adaptors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4B-08Z	96	360
Durakote plating	ZD	4B-08ZD	360	720
Zinc-nickel plating	ZN	4B-08ZN	1000	-