


ADAPTER**CB**

BSP MALE 60° SEAT / BSP FEMALE 60° CONE RUN TEE

PART NO.	THREAD				DIMENSIONS				
	E	F	G		A	B	C	S1	S2
CB-02Z	G1/8"X28	G1/8"X28	G1/8"X28		19.8	19.8	5.5	11	14
CB-04Z	G1/4"X19	G1/4"X19	G1/4"X19		25	25	5.5	14	19
CB-06Z	G3/8"X19	G3/8"X19	G3/8"X19		27.5	27.5	6.3	16	22
CB-08Z	G1/2"X14	G1/2"X14	G1/2"X14		34.5	34.5	7.5	22	27
CB-10Z	G5/8"X14	G5/8"X14	G5/8"X14		35	35	9.5	22	30
CB-12Z	G3/4"X14	G3/4"X14	G3/4"X14		40	40	10.9	27	32
CB-16Z	G1"X11	G1"X11	G1"X11		46	46	11.7	33	41
CB-20Z	G1.1/4"X11	G1.1/4"X11	G1.1/4"X11		50.5	50.5	10.1	41	50
CB-24Z	G1.1/2"X11	G1.1/2"X11	G1.1/2"X11		57.5	57.5	12.5	48	55
CB-32Z	G2"X11	G2"X11	G2"X11		72.5	72.5	16.1	63	70

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	CB-08Z
304 stainless steel	SR	CB-08SR
316L stainless steel	SV	CB-08SV
316Ti stainless steel	SY	CB-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	CB-08Z	96	360
Durakote plating	ZD	CB-08ZD	360	720
Zinc-nickel plating	ZN	CB-08ZN	1000	-