


ADAPTER**1KT-SP**

METRIC MALE 60° CONE / BSPT MALE

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	L	S1	
1KT-14-04SPZ	M14X1.5	R1/4"X19			17	14.5	37.5	14	
1KT-14-06SPZ	M14X1.5	R3/8"X19			17	15	38	17	
1KT-16-06SPZ	M16X1.5	R3/8"X19			18	15	39	17	
1KT-18-06SPZ	M18X1.5	R3/8"X19			18	15	39	19	
1KT-20-06SPZ	M20X1.5	R3/8"X19			20	15	43	22	
1KT-22-06SPZ	M22X1.5	R3/8"X19			20	15	43	24	
1KT-22-08SPZ	M22X1.5	R1/2"X14			20	20	48	24	
1KT-24-08SPZ	M24X1.5	R1/2"X14			21.5	20	51.5	27	
1KT-24-12SPZ	M24X1.5	R3/4"X14			21.5	20	51.5	30	
1KT-30-12SPZ	M30X1.5	R3/4"X14			26	20	57	32	
1KT-33-16SPZ	M33X1.5	R1"X11			30	25.5	66.5	36	
1KT-36-20SPZ	M36X1.5	R1.1/4"X11			33	26.5	72.5	46	
1KT-42-24SPZ	M42X1.5	R1.1/2"X11			36	26.5	77.5	50	

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	1KT-22-08SPZ
304 stainless steel	SR	1KT-22-08SPSR
316L stainless steel	SV	1KT-22-08SPSV
316Ti stainless steel	SY	1KT-22-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1KT-22-08SPZ	96	360
Durakote plating	ZD	1KT-22-08SPZD	360	720
Zinc-nickel plating	ZN	1KT-22-08SPZN	1000	-