


ADAPTER

**4S**

JIS GAS MALE 60° CONE PLUG

PART NO.	THREAD				DIMENSIONS				
	E				A	L	S1		
4S-02Z	G1/8"X28				12	18	14		
4S-04Z	G1/4"X19				16	24	17		
4S-06Z	G3/8"X19				18	24	19		
4S-08Z	G1/2"X14				20	28	22		
4S-12Z	G3/4"X14				22	33	30		
4S-16Z	G1"X11				24	35	36		
4S-20Z	G1.1/4"X11				27	40	46		
4S-24Z	G1.1/2"X11				27	42	50		
4S-32Z	G2"X11				30	47	65		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	4S-08Z
304 stainless steel	SR	4S-08SR
316L stainless steel	SV	4S-08SV
316Ti stainless steel	SY	4S-08SY

2. Plating options and performance for carbon steel adaptors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4S-08Z	96	360
Durakote plating	ZD	4S-08ZD	360	720
Zinc-nickel plating	ZN	4S-08ZN	1000	-