


ADAPTER**5GB**

BSP MALE O-RING / BSP FEMALE

PART NO.	THREAD		O-RING	DIMENSIONS					
	E	F		A	L	S1			
5GB-04Z	G1/4"X19	G1/4"X19	O111	11.2	32	19			
5GB-04-06Z	G1/4"X19	G3/8"X19	O111	11.2	35.5	22			
5GB-06Z	G3/8"X19	G3/8"X19	O113	11.5	36	24			
5GB-06-08Z	G3/8"X19	G1/2"X14	O113	11.5	41	27			
5GB-08Z	G1/2"X14	G1/2"X14	O17.862.62	14	41	27			
5GB-08-12Z	G1/2"X14	G3/4"X14	O17.862.62	14	44.5	36			
5GB-12Z	G3/4"X14	G3/4"X14	O119	14.5	44.5	36			
5GB-12-16Z	G3/4"X14	G1"X11	O119	14.5	50	41			
5GB-16-12Z	G1"X11	G3/4"X14	O217	18.6	45.5	41			
5GB-16Z	G1"X11	G1"X11	O217	18.6	51	41			

1. Material options for connector and the O-ring.

Connector material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	5GB-08Z
304 stainless steel	Viton	SR	5GB-08SR
316L stainless steel	Viton	SV	5GB-08SV
316Ti stainless steel	Viton	SY	5GB-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	5GB-08Z	96	360
Durakote plating	ZD	5GB-08ZD	360	720
Zinc-nickel plating	ZN	5GB-08ZN	1000	-