


ADAPTER**1OT-SP**

SAE O-RING BOSS/BSPT MALE

PART NO.	THREAD		O-RING		DIMENSIONS				
	E	F	E		A	B	L	S1	
1OT-04SPZ	7/16"X20	R1/4"X19	O904		9.10	14.5	29.5	17	
1OT-06SPZ	9/16"X18	R3/8"X19	O906		9.93	15	30.5	17	
1OT-06-04SPZ	9/16"X18	R1/4"X19	O906		9.93	14.5	30	19	
1OT-08-04SPZ	3/4"X16	R1/4"X19	O908		11.13	14.5	33.5	22	
1OT-08-06SPZ	3/4"X16	R3/8"X19	O908		11.13	15	34	22	
1OT-08SPZ	3/4"X16	R1/2"X14	O908		11.13	20	38	22	
1OT-10-06SPZ	7/8"X14	R3/8"X19	O910		12.7	15	37.5	27	
1OT-10-08SPZ	7/8"X14	R1/2"X14	O910		12.7	20	42.5	27	
1OT-12-08SPZ	1.1/16"X12	R1/2"X14	O912		15.09	20	46	32	
1OT-12SPZ	1.1/16"X12	R3/4"X14	O912		15.09	20	46	32	
1OT-16-12SPZ	1.5/16"X12	R3/4"X14	O916		15.09	20	46	38	
1OT-16SPZ	1.5/16"X12	R1"X11	O916		15.09	25.5	51	38	
1OT-20-16SPZ	1.5/8"X12	R1"X11	O920		15.09	25.5	55.5	50	

1. Material options for connector body and the O-ring.

Connector body material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	1OT-08SPZ
304 stainless steel	Viton	SR	1OT-08SPSR
316L stainless steel	Viton	SV	1OT-08SPSV
316Ti stainless steel	Viton	SY	1OT-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1OT-08SPZ	96	360
Durakote plating	ZD	1OT-08SPZD	360	720
Zinc-nickel plating	ZN	1OT-08SPZN	1000	-