


ADAPTER**2TB9-SP**

BSPT MALE / BSP FEMALE 60° CONE 90° ELBOW

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	S1	S2	
2TB9-02SPZ	R1/8"X28	G1/8"X28			21	5.5	11	14	
2TB9-04SPZ	R1/4"X19	G1/4"X19			25.5	5.5	14	19	
2TB9-06SPZ	R3/8"X19	G3/8"X19			28.5	6.3	16	22	
2TB9-06-08SPZ	R3/8"X19	G1/2"X14			31	7.5	19	27	
2TB9-08-06SPZ	R1/2"X14	G3/8"X19			36	6.3	22	22	
2TB9-08SPZ	R1/2"X14	G1/2"X14			36	7.5	22	27	
2TB9-08-12SPZ	R1/2"X14	G3/4"X14			37	10.9	24	32	
2TB9-12-08SPZ	R3/4"X14	G1/2"X14			43.5	7.5	27	27	
2TB9-12SPZ	R3/4"X14	G3/4"X14			43.5	10.9	27	32	
2TB9-16SPZ	R1"X11	G1"X11			50	11.7	33	41	
2TB9-20SPZ	R1.1/4"X11	G1.1/4"X11			57	10.1	41	50	
2TB9-24SPZ	R1.1/2"X11	G1.1/2"X11			62.5	12.5	48	55	

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2TB9-08SPZ
304 stainless steel	SR	2TB9-08SPSR
316L stainless steel	SV	2TB9-08SPSV
316Ti stainless steel	SY	2TB9-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2TB9-08SPZ	96	360
Durakote plating	ZD	2TB9-08SPZD	360	720
Zinc-nickel plating	ZN	2TB9-08SPZN	1000	-