


ADAPTER**4T-SP**

BSPT MALE PLUG

PART NO.	THREAD				DIMENSIONS				
	E				A	L	S1		
4T-02SPZ	R1/8"X28				10	16	12		
4T-04SPZ	R1/4"X19				14.5	20	14		
4T-06SPZ	R3/8"X19				15	21	17		
4T-08SPZ	R1/2"X14				20	27	22		
4T-12SPZ	R3/4"X14				20	29	27		
4T-16SPZ	R1"X11				25.5	36.5	36		
4T-20SPZ	R1.1/4"X11				26.5	38.5	46		
4T-24SPZ	R1.1/2"X11				26.5	42	50		
4T-32SPZ	R2"X11				30	47	65		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	4T-12SPZ
304 stainless steel	SR	4T-12SPSR
316L stainless steel	SV	4T-12SPSV
316Ti stainless steel	SY	4T-12SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4T-12SPZ	96	360
Durakote plating	ZD	4T-12SPZD	360	720
Zinc-nickel plating	ZN	4T-12SPZN	1000	-