


ADAPTER



5JT

JIC MALE 74° CONE / BSPT FEMALE

PART NO.	THREAD				DIMENSIONS					
	E	F			A	L	S1			
5JT-04-02Z	7/16"X20	Rc1/8"X28			14	30	14			
5JT-04Z	7/16"X20	Rc1/4"X19			14	35.5	19			
5JT-06-04Z	9/16"X18	Rc1/4"X19			14.1	35.5	19			
5JT-06Z	9/16"X18	RC3/8"X19			14.1	36.5	22			
5JT-08-06Z	3/4"X16	RC3/8"X19			16.7	39.5	22			
5JT-08Z	3/4"X16	Rc1/2"X14			16.7	45.5	27			
5JT-10-08Z	7/8"X14	Rc1/2"X14			19.3	48	27			
5JT-12Z	1.1/16"X12	Rc3/4"X14			21.9	52.5	36			
5JT-16Z	1.5/16"X12	Rc1"X11			23.1	59	41			

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5JT-08Z
304 stainless steel	SR	5JT-08SR
316L stainless steel	SV	5JT-08SV
316Ti stainless steel	SY	5JT-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	5JT-08Z	96	360
Durakote plating	ZD	5JT-08ZD	360	720
Zinc-nickel plating	ZN	5JT-08ZN	1000	-