



5T9-SP

BSPT MALE / BSPT FEMALE 90° ELBOW

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	S1		
5T9-02SPZ	R1/8"X28	Rc1/8"X28			24.5	23	16		
5T9-04SPZ	R1/4"X19	Rc1/4"X19			28.5	25	19		
5T9-06SPZ	R3/8"X19	Rc3/8"X19			33.5	25	24		
5T9-08SPZ	R1/2"X14	Rc1/2"X14			40.8	31.5	30		
5T9-12SPZ	R3/4"X14	Rc3/4"X14			47.5	37	33		
5T9-16SPZ	R1"X11	Rc1"X11			56.5	43	41		
5T9-20SPZ	R1.1/4"X11	Rc1.1/4"X11			61	50	48		
5T9-24SPZ	R1.1/2"X11	Rc1.1/2"X11			75	55	63		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5T9-08SPZ
304 stainless steel	SR	5T9-08SPSR
316L stainless steel	SV	5T9-08SPSV
316Ti stainless steel	SY	5T9-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	5T9-08SPZ	96	360
Durakote plating	ZD	5T9-08SPZD	360	720
Zinc-nickel plating	ZN	5T9-08SPZN	1000	-