


ADAPTER**5TB9-SP**

BSPT MALE/BSP FEMALE 90° ELBOW

PART NO.	THREAD				DIMENSIONS				
	E	F			A	B	S1		
5TB9-02SPZ	R1/8"X28	G1/8"X28			24.5	20	16		
5TB9-04SPZ	R1/4"X19	G1/4"X19			28.5	22	19		
5TB9-06SPZ	R3/8"X19	G3/8"X19			33.5	26	24		
5TB9-08SPZ	R1/2"X14	G1/2"X14			40.5	31	30		
5TB9-12SPZ	R3/4"X14	G3/4"X14			47.5	37	33		
5TB9-16SPZ	R1"X11	G1"X11			56.5	43	41		

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5TB9-08SPZ
304 stainless steel	SR	5TB9-08SPSR
316L stainless steel	SV	5TB9-08SPSV
316Ti stainless steel	SY	5TB9-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	5TB9-08SPZ	96	360
Durakote plating	ZD	5TB9-08SPZD	360	720
Zinc-nickel plating	ZN	5TB9-08SPZN	1000	-