


ADAPTER



5TN-SP

BSPT MALE / NPT FEMALE

PART NO.	THREAD				DIMENSIONS				
	E	F			A	L	S1		
5TN-02SPZ	R1/8"X28	Z1/8"X27			10	25	17		
5TN-04-02SPZ	R1/4"X19	Z1/8"X27			14.5	21.5	14		
5TN-04SPZ	R1/4"X19	Z1/4"X18			14.5	34.5	19		
5TN-06-04SPZ	R3/8"X19	Z1/4"X18			15	23	19		
5TN-06SPZ	R3/8"X19	Z3/8"X18			15	36.5	24		
5TN-08-06SPZ	R1/2"X14	Z3/8"X18			20	28.5	24		
5TN-08SPZ	R1/2"X14	Z1/2"X14			20	47	30		
5TN-12-08SPZ	R3/4"X14	Z1/2"X14			20	30.5	32		
5TN-12SPZ	R3/4"X14	Z3/4"X14			20	49	36		
5TN-16-12SPZ	R1"X11	Z3/4"X14			25.5	36.5	36		
5TN-16SPZ	R1"X11	Z1"X11.5			25.5	59	41		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5TN-08SPZ
304 stainless steel	SR	5TN-08SPSR
316L stainless steel	SV	5TN-08SPSV
316Ti stainless steel	SY	5TN-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	5TN-08SPZ	96	360
Durakote plating	ZD	5TN-08SPZD	360	720
Zinc-nickel plating	ZN	5TN-08SPZLN	1000	-