


ADAPTER**4H-N**

METRIC MALE ORING SEAL PLUG

REF. ISO 6149-4

PART NO.	THREAD		O-RING		DIMENSIONS				
	E		E		A	L	S1		
4H-10NZ	M10X1		O08.1X1.6		9.5	17	14		
4H-12NZ	M12X1.5		O09.3X2.2		11	18.5	17		
4H-14NZ	M14X1.5		O11.3X2.2		11	19.5	19		
4H-16NZ	M16X1.5		O13.3X2.2		12.5	22	22		
4H-18NZ	M18X1.5		O15.3X2.2		14	24	24		
4H-20NZ	M20X1.5		O17.3X2.2		14	25	27		
4H-22NZ	M22X1.5		O19.3X2.2		15	26	27		
4H-27NZ	M27X2		O23.6X2.9		18.5	31.5	32		
4H-30NZ	M30X2		O26.6X2.9		18.5	33	36		
4H-33NZ	M33X2		O29.6X2.9		18.5	34	41		
4H-42NZ	M42X2		O38.6X2.9		19	36.5	50		

1. Material options for connector body and the O-ring.

Connector body material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	4H-22NZ
304 stainless steel	Viton	SR	4H-22NSR
316L stainless steel	Viton	SV	4H-22NSV
316Ti stainless steel	Viton	SY	4H-22NSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4H-22NZ	96	360
Durakote plating	ZD	4H-22NZD	360	720
Zinc-nickel plating	ZN	4H-22NZN	1000	-