


ADAPTER**4MN-WD**

METRIC MALE CAPTIVE SEAL HOLLOW HEX PLUG

REF. ISO 9974-4

PART NO.	THREAD		CAPTIVE SEAL		DIMENSIONS				
	E		E		A	L	S1		
4MN-10WDZ	M10X1		WD-B02		8	12	5		
4MN-12WDZ	M12X1.5		WD-M12		12	17	6		
4MN-14WDZ	M14X1.5		WD-M14		12	17	6		
4MN-16WDZ	M16X1.5		WD-M16		12	17	8		
4MN-18WDZ	M18X1.5		WD-M18		12	17	8		
4MN-20WDZ	M20X1.5		WD-M20		14	19	10		
4MN-22WDZ	M22X1.5		WD-M22		14	19	10		
4MN-26WDZ	M26X1.5		WD-B12		16	21	12		
4MN-27WDZ	M27X2		WD-B12		16	21	12		
4MN-33WDZ	M33X2		WD-B16		16	23	17		
4MN-42WDZ	M42X2		WD-B20		16	23	22		
4MN-48WDZ	M48X2		WD-B24		16	23	24		

1. Material options for connector body and the captive seal.

Connector body material	Captive seal material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	4MN-22WDZ
304 stainless steel	Viton	SR	4MN-22WDSR
316L stainless steel	Viton	SV	4MN-22WDSV
316Ti stainless steel	Viton	SY	4MN-22WDSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4MN-22WDZ	96	360
Durakote plating	ZD	4MN-22WDZD	360	720
Zinc-nickel plating	ZN	4MN-22WDZN	1000	-