


ADAPTER**7NU-S**

NPT FEMALE / NPSM FEMALE 60° CONE

PART NO.	THREAD				DIMENSIONS				
	E	F			B	L	S1	S2	
7NU-02SZ	Z1/8"X27	1/8"X27			3.5	24	17	15	
7NU-04-02SZ	Z1/4"X18	1/8"X27			3.5	29	19	15	
7NU-04SZ	Z1/4"X18	1/4"X18			4.6	31.5	19	19	
7NU-04-06SZ	Z1/4"X18	3/8"X18			6	31.5	19	22	
7NU-06SZ	Z3/8"X18	3/8"X18			6	34	22	22	
7NU-06-08SZ	Z3/8"X18	1/2"X14			7.5	34	22	27	
7NU-08-06SZ	Z1/2"X14	3/8"X18			6	39	30	22	
7NU-08SZ	Z1/2"X14	1/2"X14			7.5	41	30	27	
7NU-12SZ	Z3/4"X14	3/4"X14			8.9	44	36	32	
7NU-16SZ	Z1"X11.5	1"X11.5			10.5	51.5	41	41	
7NU-20SZ	Z1.1/4"X11.5	1.1/4"X11.5			11.1	55	50	50	
7NU-24SZ	Z1.1/2"X11.5	1.1/2"X11.5			11.2	55.5	60	55	
7NU-32SZ	Z2"X11.5	2"X11.5			11.5	57	70	70	

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	7NU-08SZ
304 stainless steel	SR	7NU-08SSR
316L stainless steel	SV	7NU-08SSV
316Ti stainless steel	SY	7NU-08SSY

2. Plating options and performance for carbon steel adaptors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	7NU-08SZ	96	360
Durakote plating	ZD	7NU-08SZD	360	720
Zinc-nickel plating	ZN	7NU-08SZN	1000	-