


ADAPTER



1NO

NPT MALE / SAE O-RING BOSS L-SERIES ISO 11926-3

PART NO.	THREAD		O-RING	DIMENSIONS				
	E	F	F	A	B	L	S1	
1NO-04Z	Z1/4"X18	7/16"X20	O904	15	9.1	30.9	17	
1NO-04-06Z	Z1/4"X18	9/16"X18	O906	15	10	31	17	
1NO-06-04Z	Z3/8"X18	7/16"X20	O904	15	9.1	33	19	
1NO-06Z	Z3/8"X18	9/16"X18	O906	16	9.9	32	19	
1NO-06-08Z	Z3/8"X18	3/4"X16	O908	16	11.1	35.5	22	
1NO-08Z	Z1/2"X14	3/4"X16	O908	19.5	11.1	38.5	22	
1NO-08-10Z	Z1/2"X14	7/8"X14	O910	19.5	12.7	42	27	
1NO-08-12Z	Z1/2"X14	1.1/16"X12	O912	19.5	15.1	45.5	32	
1NO-12-10Z	Z3/4"X14	7/8"X14	O910	19.5	12.7	46.5	30	
1NO-12Z	Z3/4"X14	1.1/16"X12	O912	19.5	15.1	45.5	32	
1NO-16Z	Z1"X11.5	1.5/16"X12	O916	25.5	15.1	51.5	38	
1NO-20-16Z	Z1.1/4"X11.5	1.5/16"X12	O916	26.5	15.1	58.5	46	
1NO-20Z	Z1.1/4"X11.5	1.5/8"X12	O920	26.5	15.1	56.5	50	
1NO-24Z	Z1.1/2"X11.5	1.7/8"X12	O924	27.5	15.1	57.5	55	

1. Material options for connector body and the O-ring.

Connector body material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	1NO-08Z
304 stainless steel	Viton	SR	1NO-08SR
316L stainless steel	Viton	SV	1NO-08SV
316Ti stainless steel	Viton	SY	1NO-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1NO-08Z	96	360
Durakote plating	ZD	1NO-08ZD	360	720
Zinc-nickel plating	ZN	1NO-08ZN	1000	-