


ADAPTER



LN

NPT MALE/NPT FEMALE RUN TEE

PART NO.	THREAD			DIMENSIONS					
	E	F	G			A	B	C	S1
LN-02Z	Z1/8"X27	Z1/8"X27	Z1/8"X27			24.5	24.5	18	16
LN-04Z	Z1/4"X18	Z1/4"X18	Z1/4"X18			28	28	22.5	19
LN-06Z	Z3/8"X18	Z3/8"X18	Z3/8"X18			33.5	33.5	25	24
LN-08Z	Z1/2"X14	Z1/2"X14	Z1/2"X14			41.2	41.2	31.2	30
LN-12Z	Z3/4"X14	Z3/4"X14	Z3/4"X14			46.5	46.5	34.5	33
LN-16Z	Z1"X11.5	Z1"X11.5	Z1"X11.5			54.5	54.5	41.1	41
LN-20Z	Z1.1/4"X11.5	Z1.1/4"X11.5	Z1.1/4"X11.5			58.5	58.5	43.5	48
LN-24Z	Z1.1/2"X11.5	Z1.1/2"X11.5	Z1.1/2"X11.5			71.5	71.5	52.8	63

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	LN-08Z
304 stainless steel	SR	LN-08SR
316L stainless steel	SV	LN-08SV
316Ti stainless steel	SY	LN-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	LN-08Z	96	360
Durakote plating	ZD	LN-08ZD	360	720
Zinc-nickel plating	ZN	LN-08ZN	1000	-