


ADAPTER**5NO**

NPT MALE / SAE FEMALE ISO 11926-1

PART NO.	THREAD		DIMENSIONS						
	E	F			A	L	S1		
5NO-02-04Z	Z1/8"X27	7/16"X20			10.5	29.5	17		
5NO-02-05Z	Z1/8"X27	1/2"X20			10.5	30.5	17		
5NO-04Z	Z1/4"X18	7/16"X20			15	34	17		
5NO-04-06Z	Z1/4"X18	9/16"X18			15	36	19		
5NO-04-08Z	Z1/4"X18	3/4"X16			15	41	27		
5NO-06-04Z	Z3/8"X18	7/16"X20			16	22	19		
5NO-06Z	Z3/8"X18	9/16"X18			16	34.5	19		
5NO-06-08Z	Z3/8"X18	3/4"X16			16	40	24		
5NO-08-06Z	Z1/2"X14	9/16"X18			19.5	27.5	24		
5NO-08Z	Z1/2"X14	3/4"X16			19.5	41.5	27		
5NO-08-10Z	Z1/2"X14	7/8"X14			19.5	46.5	30		
5NO-12-08Z	Z3/4"X14	3/4"X16			19.8	29.5	30		
5NO-12-10Z	Z3/4"X14	7/8"X14			19.5	42.5	30		
5NO-12Z	Z3/4"X14	1.1/16"X12			19.5	47	36		
5NO-16-12Z	Z1"X11.5	1.1/16"X12			25.5	52.5	36		
5NO-16Z	Z1"X11.5	1.5/16"X12			25.5	53	41		
5NO-20Z	Z1.1/4"X11.5	1.5/8"X12			26.5	55.5	50		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5NO-12Z
304 stainless steel	SR	5NO-12SR
316L stainless steel	SV	5NO-12SV
316Ti stainless steel	SY	5NO-12SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	5NO-12Z	96	360
Durakote plating	ZD	5NO-12ZD	360	720
Zinc-nickel plating	ZN	5NO-12ZN	1000	-