


ADAPTER



AF

ORFS MALE O-RING TEE

REF. ISO 8434-3

PART NO.	THREAD			O-RING			DIMENSIONS			
	E	F	G	E	F	G	A	B	C	S1
AF-04Z	9/16"X18	9/16"X18	9/16"X18	O011	O011	O011	23	23	23	14
AF-06Z	11/16"X16	11/16"X16	11/16"X16	O012	O012	O012	27	27	27	19
AF-08Z	13/16"X16	13/16"X16	13/16"X16	O014	O014	O014	31	31	31	22
AF-10Z	1"X14	1"X14	1"X14	O016	O016	O016	36.5	36.5	36.5	27
AF-12Z	1.3/16"X12	1.3/16"X12	1.3/16"X12	O018	O018	O018	40.3	40.3	40.3	30
AF-16Z	1.7/16"X12	1.7/16"X12	1.7/16"X12	O021	O021	O021	44.5	44.5	44.5	36
AF-20Z	1.11/16"X12	1.11/16"X12	1.11/16"X12	O025	O025	O025	44.5	44.5	44.5	41
AF-24Z	2"X12	2"X12	2"X12	O029	O029	O029	53.5	53.5	53.5	50

1. Material options for connector body and the O-ring.

Connector body material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	AF-10Z
304 stainless steel	Viton	SR	AF-10SR
316L stainless steel	Viton	SV	AF-10SV
316Ti stainless steel	Viton	SY	AF-10SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	AF-10Z	96	360
Durakote plating	ZD	AF-10ZD	360	720
Zinc-nickel plating	ZN	AF-10ZN	1000	-