


INTERLOCK HOSE FITTING



JIC FEMALE 74° CONE SEAT DOUBLE HEXAGON

REF. ISO 12151-5 / SAE J516

26713D

PART NO.	E THREAD E	HOSE SIZE			DIMENSIONS			
		DN	DASH		A	C	S1	S2
26713D-20-20WZ	1.5/8"X12	32	20		45.3	16.5	50	50
26713D-24-24WZ	1.7/8"X12	40	24		50.2	20	50	60
26713D-32-32WZ	2.1/2"X12	50	32		52	23.5	65	75

1. Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	TZ/WZ	26713D-20-20WZ
304 stainless steel	SRT/SRW	26713D-20-20SRW
316L stainless steel	SVT/SVW	26713D-20-20SVW
316Ti stainless steel	SYT/SYW	26713D-20-20SYW

2. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	26713D-20-20WZ	96	360
Durakote plating	ZD	26713D-20-20WZD	360	720
Zinc-nickel plating	ZN	26713D-20-20WZN	1000	-