


HOSE FITTING



90° JIC COMPACT FEMALE 74° CONE SEAT

REF. ISO 12151-5 / SAE J516

26791KY

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS				
BRAIDED	SPIRAL		DN	DASH	A	C	H	S1	S2
26791KY-04-04Z *	-	7/16"X20	6	04	17.5	9	18	11	14
26791KY-06-04Z	-	9/16"X18	6	04	20	10	20.5	14	19
26791KY-06-06Z *	26792KY-06-06Z	9/16"X18	10	06	20	10	20.5	16	19
26791KY-08-06Z	26792KY-08-06Z	3/4"X16	10	06	23	11	25	19	22
26791KY-08-08Z *	26792KY-08-08Z	3/4"X16	12	08	23.5	11	25	22	22
26791KY-10-08Z	26792KY-10-08Z	7/8"X14	12	08	25	13	27	22	27
26791KY-10-10Z	26792KY-10-10Z	7/8"X14	16	10	24.5	13	27	22	27
26791KY-12-12Z	26792KY-12-12Z	1.1/16"X12	20	12	29	15	31	27	32
26791KY-16-16Z	26792KY-16-16Z	1.5/16"X12	25	16	43	16	34.3	33	41

1. Part no. marked with "*" is recommended.

2. The recommended match hoses for 1 piece braided fittings are : FC687/EC115-16 and smaller sizes; GH663/EC881-20 and smaller sizes; FC686/EC210/EC215/GH781-24 and smaller sizes; EC110/GH793 whole sizes etc. and with non-skive crimping. For 1 piece spiral fittings are: 2755/GH493/EC640/GH425-16 and smaller sizes; GH506/EC512-12 and larger sizes with skive crimping.

3. Carbon steel material for fitting.

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	26791K-08-08Z	96	360
Durakote plating	ZD	26791K-08-08ZD	360	720
Zinc-nickel plating	ZN	26791K-08-08ZN	1000	-