


PUSH-ON FITTING



NPT MALE

15610

REF. SAE J516

PART NO.	E THREAD E	HOSE SIZE			DIMENSIONS			
		DN	DASH		A	C	S1	
15610-02-04Z	Z 1/8"X27	6	04		18.2	10.5	12	
15610-04-04Z	Z 1/4"X18	6	04		22.7	15	14	
15610-04-06Z	Z 1/4"X18	10	06		22.5	15	14	
15610-06-06Z	Z 3/8"X18	10	06		23.5	16	19	
15610-06-08Z	Z 3/8"X18	12	08		23.7	16	19	
15610-08-08Z	Z 1/2"X14	12	08		29	19.5	22	
15610-08-10Z	Z 1/2"X14	16	10		29	19.5	22	
15610-12-12Z	Z 3/4"X14	20	12		31.4	19.5	27	

1. Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	TZ/WZ	15610-08-08Z
304 stainless steel	SRT/SRW	15610-08-08SR
316L stainless steel	SVT/SVW	15610-08-08SV
316Ti stainless steel	SYT/SYW	15610-08-08SY

2. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	15610-08-08Z	96	360
Durakote plating	ZD	15610-08-08ZD	360	720
Zinc-nickel plating	ZN	15610-08-08ZN	1000	-