


PUSH-ON FITTING



JIC MALE 74° CONE

16710

REF. ISO 12151-5 / SAE J516

PART NO.	E THREAD E	HOSE SIZE			DIMENSIONS			
		DN	DASH		A	C	S1	
16710-04-04Z	7/16"X20	6	04		22	14	14	
16710-06-04Z	9/16"X18	6	04		22	14.1	17	
16710-06-06Z	9/16"X18	10	06		22	14.1	17	
16710-08-06Z	3/4"X16	10	06		27.2	16.7	22	
16710-08-08Z	3/4"X16	12	08		26.2	16.7	22	
16710-10-10Z	7/8"X14	16	10		28.7	19.3	24	
16710-10-12Z	7/8"X14	20	12		29.4	19.3	24	
16710-12-08Z	1.1/16"X12	12	08		34.5	21.9	27	
16710-12-10Z	1.1/16"X12	16	10		34	21.9	27	
16710-12-12Z	1.1/16"X12	20	12		35.9	21.9	30	

1. Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	TZ/WZ	16710-08-08Z
304 stainless steel	SRT/SRW	16710-08-08SR
316L stainless steel	SVT/SVW	16710-08-08SV
316Ti stainless steel	SYT/SYW	16710-08-08SY

2. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	16710-08-08Z	96	360
Durakote plating	ZD	16710-08-08ZD	360	720
Zinc-nickel plating	ZN	16710-08-08ZN	1000	-