


Better Quality, Better Connection.

PUSH-ON FITTING



BSP FEMALE 60° CONE

22610

REF. ISO 12151-6

PART NO.	E THREAD E	HOSE SIZE			DIMENSIONS			
		DN	DASH		A	D	S2	
22610-04-04Z	G1/4"X19	6	04		14.7	5.5	19	
22610-06-06Z	G3/8"X19	10	06		16.5	6.3	22	
22610-08-08Z	G1/2"X14	12	08		18.2	7.5	27	
22610-12-12Z	G3/4"X14	20	12		19.9	10.9	32	

1. Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	TZ/WZ	22610-08-08Z
304 stainless steel	SRT/SRW	22610-08-08SR
316L stainless steel	SVT/SVW	22610-08-08SV
316Ti stainless steel	SYT/SYW	22610-08-08SY

2. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	22610-08-08Z	96	360
Durakote plating	ZD	22610-08-08ZD	360	720
Zinc-nickel plating	ZN	22610-08-08ZN	1000	-