


Better Quality, Better Connection.

PUSH-ON FITTING



JIC FEMALE 74° CONE SEAT

26710

REF. ISO 12151-5 / SAE J516

PART NO.	E THREAD E	HOSE SIZE			DIMENSIONS			
		DN	DASH		A	C	S2	
26710-04-04Z	7/16"X20	6	04		12.2	9	15	
26710-05-04Z	1/2"X20	6	04		12.2	9.5	17	
26710-06-06Z	9/16"X18	10	06		12.5	10.5	19	
26710-08-06Z	3/4"X16	10	06		12.5	11	24	
26710-08-08Z	3/4"X16	12	08		14.7	11	24	
26710-10-08Z	7/8"X14	12	08		15.2	13	27	
26710-10-10Z	7/8"X14	16	10		15.7	13	27	
26710-12-12Z	1.1/16"X12	20	12		17.4	15	32	
26710-16-16Z	1.5/16"X12	25	16		18.6	16	41	

1. Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	TZ/WZ	26710-08-08Z
304 stainless steel	SRT/SRW	26710-08-08SR
316L stainless steel	SVT/SVW	26710-08-08SV
316Ti stainless steel	SYT/SYW	26710-08-08SY

2. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	26710-08-08Z	96	360
Durakote plating	ZD	26710-08-08ZD	360	720
Zinc-nickel plating	ZN	26710-08-08ZN	1000	-