



HOSE FITTING



BSP MALE 60° CONE SEAT

12611
1261212611A
12612A

REF. ISO 12151-6

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S1	
ONLY USE FOR 60° CONE SEAT WITH SMALL HEX									
12611-02-03Z	-	G1/8"X28	5	03		22	10	12	
12611-04-04Z	-	G1/4"X19	6	04		24.5	12	14	
12611-06-05Z	-	G3/8"X19	8	05		26	13.5	17	
12611-06-06Z	12612-06-06Z	G3/8"X19	10	06		26	13.5	17	
12611-06-08Z	12612-06-08Z	G3/8"X19	12	08		26.5	13.5	19	
12611-08-06Z	12612-08-06Z	G1/2"X14	10	06		30.5	16	22	
12611-08-08Z	12612-08-08Z	G1/2"X14	12	08		31	16	22	
12611-10-08Z	12612-10-08Z	G5/8"X14	12	08		32.5	17.5	24	
12611-10-10Z	12612-10-10Z	G5/8"X14	16	10		33.5	17.5	24	
12611-12-08Z	12612-12-08Z	G3/4"X14	12	08		35.5	18.5	27	
12611-12-10Z	12612-12-10Z	G3/4"X14	16	10		36.5	18.5	27	
12611-12-12Z	12612-12-12Z	G3/4"X14	20	12		36.5	18.5	27	
12611-16-12Z	12612-16-12Z	G1"X11	20	12		40.5	20.5	36	
12611-16-16Z	12612-16-16Z	G1"X11	25	16		41.5	20.5	36	
12611-20-16Z	12612-20-16Z	G1.1/4"X11	25	16		43.5	20.5	46	
12611-20-20Z	12612N-20-20Z	G1.1/4"X11	32	20		46.5/49.1	20.5	46	
12611-24-20Z	12612N-24-20Z	G1.1/2"X11	32	20		49/51.6	23	50	
12611-24-24Z	12612N-24-24Z	G1.1/2"X11	40	24		49/52	23	50	
12611-32-32Z	12612N-32-32Z	G2"X11	50	32		53.5/57.9	25.5	65	
DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL WITH LARGER HEX									
12611A-02-03Z	-	G1/8"X28	5	03		22	10	14	
12611A-04-04Z *	-	G1/4"X19	6	4		24.5	12	19	
12611A-04-05Z	-	G1/4"X19	8	05		24.5	12	19	
12611A-06-05Z	-	G3/8"X19	8	5		26	13.5	22	
12611A-06-06Z *	12612A-06-06Z	G3/8"X19	10	06		28	13.5	22	
12611A-06-08Z *	12612A-06-08Z	G3/8"X19	12	8		28.5	13.5	22	
12611A-08-06Z *	12612A-08-06Z	G1/2"X14	10	06		33	16	27	
12611A-08-08Z *	12612A-08-08Z	G1/2"X14	12	8		33	16	27	
12611A-08-10Z	12612A-08-10Z	G1/2"X14	16	10		34	16	27	
12611A-10-08Z	12612A-10-08Z	G5/8"X14	12	8		35	17.5	30	
12611A-10-10Z	12612A-10-10Z	G5/8"X14	16	10		35.5	17.5	30	
12611A-12-08Z	12612A-12-08Z	G3/4"X14	12	8		36.5	18.5	32	
12611A-12-10Z	12612A-12-10Z	G3/4"X14	16	10		37.5	18.5	32	
12611A-12-12Z *	12612A-12-12Z *	G3/4"X14	20	12		37.5	18.5	32	
12611A-16-12Z	12612A-16-12Z *	G1"X11	20	12		42.5	20.5	41	
12611A-16-16Z *	12612A-16-16Z *	G1"X11	25	16		43.5	20.5	41	
12611A-20-16Z	12612A-20-16Z	G1.1/4"X11	25	16		45.5	20.5	50	
12611A-20-20Z *	12612AN-20-20Z	G1.1/4"X11	32	20		46.5/49.1	20.5	50	
12611A-24-24Z	12612AN-24-24Z	G1.1/2"X11	40	24		49/52	23	55	
12611A-32-32Z	12612AN-32-32Z	G2"X11	50	32		54.5/58.9	25.5	70	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	12611-08-08Z
304 stainless steel	SR	12611-08-08SR
316L stainless steel	SV	12611-08-08SV
316Ti stainless steel	SY	12611-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	12611-08-08Z	96	360
Durakote plating	ZD	12611-08-08ZD	360	720
Zinc-nickel plating	ZN	12611-08-08ZN	1000	-