



HOSE FITTING



20591C-T
20592C-T



20591C
20592C

90° METRIC FEMALE 24° MULTISEAL S SERIES

PART NO.		THREAD E	HOSE SIZE		TUBE O.D.	DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	H	S2
20591C-16-04TZ	-	M16X1.5	6	04	8	30	3.5	32.5	19
20591C-18-04TZ *	-	M18X1.5	6	04	10	30	3	30.5	22
20591C-20-05TZ	-	M20X1.5	8	05	12	33	4.5	34	24
20591C-20-06TZ	20592C-20-06TZ	M20X1.5	10	06	12	34.5	4.5	35.5	24
20591C-22-06TZ *	20592C-22-06TZ	M22X1.5	10	06	14	34.5	4.5	36	27
20591C-24-08TZ *	20592C-24-08TZ	M24X1.5	12	08	16	39.5	5	43.5	30
20591C-30-10TZ	20592C-30-10TZ	M30X2	16	10	20	49	7	50.5	36
20591C-36-12TZ	20592C-36-12TZ	M36X2	20	12	25	56	6.5	55.5	41
20591C-42-16TZ	20592C-42-16TZ	M42X2	25	16	30	71	9	68.4	50
20591C-52-20TZ	20592CN-52-20TZ	M52X2	32	20	38	83/85.6	8	81.5	60

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	TZ	20591C-24-08TZ
304 stainless steel	SRT	20591C-24-08SRT
316L stainless steel	SVT	20591C-24-08SVT
316Ti stainless steel	SYT	20591C-24-08SYT

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	20591C-24-08TZ	96	360
Durakote plating	ZD	20591C-24-08TZD	360	720
Zinc-nickel plating	ZN	20591C-24-08TZN	1000	-