




HOSE FITTING



22691
22692



22691-T
22692-T



22691-W
22692-W

90° BSP FEMALE 60° CONE

REF. ISO 12151-6

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	H	S2
22691-02-03Z	-	G1/8"X28	5	03		26.5	5.5	31.5	14
22691-02-04Z	-	G1/8"X28	6	04		30	5.5	34.5	14
22691-04-03Z	-	G1/4"X19	5	03		26.5	5.5	33.5	19
22691-04-04Z	-	G1/4"X19	6	04		30	5.5	36.5	19
22691-04-05Z	-	G1/4"X19	8	05		33	5.5	39.5	19
22691-04-06Z	22692-04-06Z	G1/4"X19	10	06		30	5.5	36.5	19
22691-06-04Z	-	G3/8"X19	6	04		30	6.3	37.7	22
22691-06-05Z	-	G3/8"X19	8	05		33	6.3	40.7	22
22691-06-06Z	22692-06-06Z	G3/8"X19	10	06		35.3	6.3	43	22
22691-08-06TZ	22692-08-06TZ	G1/2"X14	10	06		35.3	7.5	41.8	27
22691-08-08Z	22692-08-08Z	G1/2"X14	12	08		41	7.5	51	27
22691-10-08Z	22692-10-08Z	G5/8"X14	12	08		41	9.5	51.5	30
22691-10-10Z	22692-10-10Z	G5/8"X14	16	10		56	9.5	56	30
22691-12-12Z	22692-12-12Z	G3/4"X14	20	12		64.9	10.9	66.1	32
22691-16-16Z	22692-16-16Z	G1"X11	25	16		76.7	11.7	73.8	41
22691-20-16TZ	22692-20-16TZ	G1.1/4"X11	25	16		76.7	10.1	72	50
22691-32-32WZ	22692N-32-32WZ	G2"X11	50	32		131.8/136.2	16.1	123.3	70
ISO 12151-6 ELBOW LENGTH									
22691-02-03H25Z	-	G1/8"X28	5	03		26.5	5.5	25	14
22691-02-04H27Z	-	G1/8"X28	6	04		30	5.5	27	14
22691-04-03H28Z	-	G1/4"X19	5	03		26.5	5.5	28	19
22691-04-04H28Z	-	G1/4"X19	6	04		30	5.5	28	19
22691-04-05H31.5Z	-	G1/4"X19	8	05		30	5.5	31.5	19
22691-04-06H34Z	-	G1/4"X19	10	06		30	5.5	34	19
22691-06-04H31TZ	-	G3/8"X19	6	04		30	6.3	31	22
22691-06-05H34TZ	-	G3/8"X19	8	05		33	6.3	34	22
22691-06-06H34Z	22692-06-06H34Z	G3/8"X19	10	06		35.3	6.3	34	22
22691-06-08H42Z	22692-06-08H42Z	G3/8"X19	12	08		43.8	6.3	42	22
22691-08-06H35TZ	22692-08-06H35TZ	G1/2"X14	10	06		35.3	7.5	35	27
22691-08-08H41Z	22692-08-08H41Z	G1/2"X14	12	08		41	7.5	41	27
22691-08-10Z	22692-08-10Z	G1/2"X14	16	10		41.5	7.5	51	27
22691-10-08H45Z	22692-10-08H45Z	G5/8"X14	12	08		41	9.5	45	30
22691-10-10H51Z	22692-10-10H51Z	G5/8"X14	16	10		56	9.5	51	30
22691-10-12H58Z	22692-10-12H58Z	G5/8"X14	20	12		61	9.5	58	30
22691-12-08TZ	22692-12-08TZ	G3/4"X14	12	08		41	10.9	47	32
22691-12-10Z	22692-12-10Z	G3/4"X14	16	10		56	10.9	56	32
22691-12-12H58Z	22692-12-12H58Z	G3/4"X14	20	12		64.9	10.9	58	32
22691-12-16H71Z	22692-12-16H71Z	G3/4"X14	25	16		74.3	10.9	71	32
22691-16-12TZ	22692-16-12TZ	G1"X11	20	12		65.5	11.7	62	41
22691-16-16H70Z	22692-16-16H70Z	G1"X11	25	16		76.7	11.7	70	41
22691-20-16H76TZ	22692-20-16H76TZ	G1.1/4"X11	25	16		76.7	10.1	76	50
22691-20-20WZ	22692N-20-20WZ	G1.1/4"X11	32	20		91.5/94.1	10.1	84.3	50
22691-24-20H92TZ	22692N-24-20H92TZ	G1.1/2"X11	32	20		91.5/94.1	12.5	92	55
22691-24-24WZ	22692N-24-24WZ	G1.1/2"X11	40	24		109.4/112.4	12.5	103	55
22691-32-24H110TZ	22692N-32-24H110TZ	G2"X11	40	24		109.4/112.4	16.1	110	70
22691-32-32H140WZ	22692N-32-32H140WZ	G2"X11	50	32		131.8/136.2	16.1	140	70

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.

Better Quality, Better Connection.

2. Part no. marked with "*" is recommended.

3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/TZ/WZ	22691-08-08Z
304 stainless steel	SR/SRT/SRW	22691-08-08SR
316L stainless steel	SV/SVT/SVW	22691-08-08SV
316Ti stainless steel	SY/SYT/SYW	22691-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	22691-08-08Z	96	360
Durakote plating	ZD	22691-08-08ZD	360	720
Zinc-nickel plating	ZN	22691-08-08ZN	1000	-