



HOSE FITTING



45° JIC FEMALE 74° CONE SEAT

REF. ISO 12151-5 / SAE J516

26741**26741-W****26742****26742-W**

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	H	S2
26741-04-03Z	-	7/16"X20	5	03		32.5	9	12.1	14
26741-04-04Z *	-	7/16"X20	6	04		35.1	9	13	14
26741-04-06Z *	-	7/16"X20	10	06		35.6	9	13.5	14
26741-05-04Z	-	1/2"X20	6	04		35.6	9.5	13.5	17
26741-05-05Z *	-	1/2"X20	8	05		37.7	9.5	14.4	17
26741-06-04Z	-	9/16"X18	6	04		35.6	10	13.5	19
26741-06-05Z	-	9/16"X18	8	05		37.7	10	14.4	19
26741-06-06Z *	26742-06-06Z	9/16"X18	10	06		38.8	10	14.8	19
26741-06-08Z	26742-06-08Z	9/16"X18	12	08		39.3	10	14.8	19
26741-08-06Z	26742-08-06Z	3/4"X16	10	06		40.2	11	16.2	22
26741-08-08Z *	26742-08-08Z	3/4"X16	12	08		45.3	11	19	22
26741-10-08Z	26742-10-08Z	7/8"X14	12	08		46.7	13	20.3	27
26741-10-10Z *	26742-10-10Z	7/8"X14	16	10		54.4	13	22.1	27
26741-10-12Z	26742-10-12Z	7/8"X14	20	12		58.9	13	22.1	27
26741-12-08Z	26742-12-08Z	1.1/16"X12	12	08		50.4	14.5	21.1	32
26741-12-10Z	26742-12-10Z	1.1/16"X12	16	10		55.1	14.5	22.8	32
26741-12-12Z *	26742-12-12Z *	1.1/16"X12	20	12		59.3	14.5	24.2	32
26741-12-16Z	26742-12-16Z	1.1/16"X12	25	16		70.3	14.5	24.2	32
26741-14-12Z	26742-14-12Z	1.3/16"X12	20	12		60.1	15	24.2	36
26741-16-12Z	26742-16-12Z	1.5/16"X12	20	12		60.9	15.18	25	41
26741-16-16Z *	26742-16-16Z *	1.5/16"X12	25	16		74.3	15.18	28.7	41
26741-16-20Z	26742N-16-20Z	1.5/16"X12	32	20		85.8/88.4	15.18	28.7	41
26741-20-20WZ	26742N-20-20WZ	1.5/8"X12	32	20		96.3/98.9	16.1	35.5	50
26741-24-20WZ	26742N-24-20WZ	1.7/8"X12	32	20		86.6/89.2	18.6	35.9	60
26741-24-24WZ	26742N-24-24WZ	1.7/8"X12	40	24		114.8/117.8	18.6	44.1	60
26741-32-32WZ	26742N-32-32WZ	2.1/2"X12	50	32		135.9/140.3	23.8	51.6	75
ISO 12151-5 SHORT ELBOW (SWE45S)									
26741-04-04H10Z	-	7/16"X20	6	04		31	9	10	14
26741-05-05H10Z	-	1/2"X20	8	05		31.8	9.5	10	17
26741-06-04H11Z	-	9/16"X18	6	04		32	10	11	19
26741-06-06H11Z	26742-06-06H11Z	9/16"X18	10	06		35.7	10	11	19
26741-08-06H15Z	26742-08-06H15Z	3/4"X16	10	06		43	11	15	22
26741-08-08H15Z	26742-08-08H15Z	3/4"X16	12	08		47.4	11	15	22
26741-10-10H16Z	26742-10-10H16Z	7/8"X14	16	10		53.4	13	16	27
26741-12-12H21Z	26742-12-12H21Z	1.1/16"X12	20	12		56.9	14.5	21	32
26741-16-16H24Z	26742-16-16H24Z	1.5/16"X12	25	16		72.5	15.18	24	41
ISO 12151-5 MEDIUM ELBOW (SWE45M)									
26741-20-20H32WZ	26742N-20-20H32WZ	1.5/8"X12	32	20		92.8/96.9	16.1	32	50
26741-24-24H42WZ	26742N-24-24H42WZ	1.7/8"X12	40	24		112.7/115.7	18.6	42	60

Better Quality, Better Connection.

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/WZ	26741-08-08Z
304 stainless steel	SR/SRW	26741-08-08SR
316L stainless steel	SV/SVW	26741-08-08SV
316Ti stainless steel	SY/SYW	26741-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	26741-08-08Z	96	360
Durakote plating	ZD	26741-08-08ZD	360	720
Zinc-nickel plating	ZN	26741-08-08ZN	1000	-