


## HOSE FITTING



**00400-D**

SOCKET FOR 4SP / 4SH / R12 HOSE

| PART NO.     |  | HOSE SIZE |      |  | DIMENSIONS |      |      |  |  |
|--------------|--|-----------|------|--|------------|------|------|--|--|
|              |  | DN        | DASH |  | L          | D    | d    |  |  |
| 00400-06DZ * |  | 10        | 06   |  | 34         | 26   | 18.4 |  |  |
| 00400-08DZ * |  | 12        | 08   |  | 37         | 29   | 21.5 |  |  |
| 00400-10DZ * |  | 16        | 10   |  | 39         | 33   | 24.8 |  |  |
| 00400-12DZ * |  | 20        | 12   |  | 45         | 37.5 | 29.4 |  |  |
| 00400-16DZ * |  | 25        | 16   |  | 56         | 46.5 | 36.5 |  |  |

- Part no. marked with "\*" is recommended.
- Matched with spiral fitting and ISO 3862 4SP / 4SH / R12, GB/T 10544 4SP / 4SH / R12, EN 856 4SP / 4SH / R12, SAE J517 100R12 spiral hose.
- Material options for socket.

| Socket material        | Part. No. suffix | Part No. example |
|------------------------|------------------|------------------|
| Carbon steel (Default) | Z                | 00400-08DZ       |
| 304 stainless steel    | SR               | 00400-08DSR      |
| 316L stainless steel   | SV               | 00400-08DSV      |
| 316Ti stainless steel  | SY               | 00400-08DSY      |

- Plating options and performance for carbon steel socket

| Plating method         | Part. No. suffix | Part No. example | White rust (Hours) | Red rust (Hours) |
|------------------------|------------------|------------------|--------------------|------------------|
| Cr3+ plating (Default) | Z                | 00400-08DZ       | 96                 | 360              |
| Durakote plating       | ZD               | 00400-08DZD      | 360                | 720              |
| Zinc-nickel plating    | ZN               | 00400-08DZN      | 1000               | -                |