


HOSE FITTING



METRIC MALE DOUBLE USE FOR 60° CONE SEAT
OR BONDED SEAL

10611
10612

REF. JIS B8363

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S1	
10611-14-04Z	-	M14X1.5	6	04		23.5	11	19	
10611-14-06Z	10612-14-06Z	M14X1.5	10	06		25	11	19	
10611-16-04Z	-	M16X1.5	6	04		27.5	12	22	
10611-16-05Z	-	M16X1.5	8	05		27.5	12	22	
10611-18-06Z	10612-18-06Z	M18X1.5	10	06		27.5	12	24	
10611-22-06Z	10612-22-06Z	M22X1.5	10	06		30.5	14	27	
10611-22-08Z	10612-22-08Z	M22X1.5	12	08		31	14	27	
10611-24-10Z	10612-24-10Z	M24X1.5	16	10		35	14	30	
10611-26-10Z	10612-26-10Z	M26X1.5	16	10		34.5	16	32	
10611-27-10DZ	10612-27-10DZ	M27X1.5	16	10		35	16	32	
10611-27-10Z	10612-27-10Z	M27X2	16	10		34.5	16	32	
10611-30-12DZ	10612-30-12DZ	M30X1.5	20	12		38	18	36	
10611-30-12Z	10612-30-12Z	M30X2	20	12		38	18	36	
10611-33-16Z	10612-33-16Z	M33X2	25	16		40	18	41	
10611-42-20Z	10612N-42-20Z	M42X2	32	20		46/48.6	20	50	
10611-45-20Z	10612N-45-20Z	M45X2	32	20		46/48.6	20	55	
10611-48-24Z	10612N-48-24Z	M48X2	40	24		46/49	20	55	
10611-52-24Z	10612N-52-24Z	M52X2	40	24		46/49	20	60	

- The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
- Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	10611-22-08Z
304 stainless steel	SR	10611-22-08SR
316L stainless steel	SV	10611-22-08SV
316Ti stainless steel	SY	10611-22-08SY

- Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	10611-22-08Z	96	360
Durakote plating	ZD	10611-22-08ZD	360	720
Zinc-nickel plating	ZN	10611-22-08ZN	1000	-