



HOSE FITTING



20411C-T
20412C-T



20411C
20412C

METRIC FEMALE 24° MULTISEAL L SERIES

PART NO.		THREAD E	HOSE SIZE		TUBE O.D.	DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S2	
20411C-12-04Z	-	M12X1.5	6	4	6	19.5	3.5	17	
20411C-14-04Z *	-	M14X1.5	6	4	8	20.5	3.5	19	
20411C-16-04TZ	-	M16X1.5	6	4	10	20.5	4	19	
20411C-16-05Z *	-	M16X1.5	8	5	10	21	3.5	22	
20411C-16-06Z	20412C-16-06Z	M16X1.5	10	6	10	21	3.5	22	
20411C-18-06TZ *	20412C-18-06TZ	M18X1.5	10	6	12	23	3	22	
20411C-22-06TZ	20412C-22-06TZ	M22X1.5	10	6	15	23	4.5	27	
20411C-22-08TZ *	20412C-22-08TZ	M22X1.5	12	8	15	25	4.5	27	
20411C-26-10TZ	20412C-26-10TZ	M26X1.5	16	10	18	26	4	32	
20411C-30-10TZ	20412C-30-10TZ	M30X2	16	10	22	26	7	36	
20411C-30-12TZ	20412C-30-12TZ	M30X2	20	12	22	26	7	36	
20411C-36-16Z	20412C-36-16Z	M36X2	25	16	28	29	6.5	41	
20411C-45-20TZ	20412CN-45-20TZ	M45X2	32	20	35	33/35.6	7	55	
20411C-52-24TZ	20412CN-52-24TZ	M52X2	40	24	42	34/37	8	60	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.

2. Part no. marked with "*" is recommended.

3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/TZ	20411C-22-08TZ
304 stainless steel	SR/SRT	20411C-22-08SRT
316L stainless steel	SV/SVT	20411C-22-08SVT
316Ti stainless steel	SY/SYT	20411C-22-08SYT

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	20411C-22-08TZ	96	360
Durakote plating	ZD	20411C-22-08TZD	360	720
Zinc-nickel plating	ZN	20411C-22-08TZN	1000	-