



HOSE FITTING



20691
20692



20691-T
20692-T

90° METRIC FEMALE 60° CONE

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S2	
20691-14-04Z *	-	M14X1.5	6	04		30	5.5	37	19
20691-16-05Z	-	M16X1.5	8	05		33	5.5	40.5	22
20691-18-06Z *	20692-18-06Z	M18X1.5	10	6		35.3	5.5	43.8	24
20691-22-08Z	20692-22-08Z	M22X1.5	12	08		41	6	52	27
20691-27-10DTZ	20692-27-10DTZ	M27X1.5	16	10		56	6	55	32
20691-30-12DZ	20692-30-12DZ	M30X1.5	20	12		66.2	6	68.5	36
20691-36-16Z	20692-36-16Z	M36X2	25	16		80	6.5	72	41
20691-39-16TZ	20692-39-16TZ	M39X2	25	16		76.7	6.5	74	46
20691-45-20TZ	20692N-45-20TZ	M45X2	32	20		91.5/94.1	8.5	85	55
20691-52-24TZ	20692N-52-24TZ	M52X2	40	24		109.4/112.4	10	99	60

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.

2. Part no. marked with "*" is recommended.

3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/TZ	20691-22-08Z
304 stainless steel	SR/SRT	20691-22-08SR
316L stainless steel	SV/SVT	20691-22-08SV
316Ti stainless steel	SY/SYT	20691-22-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	20691-22-08Z	96	360
Durakote plating	ZD	20691-22-08ZD	360	720
Zinc-nickel plating	ZN	20691-22-08ZN	1000	-