


HOSE FITTING



45° GB METRIC FEMALE 74° CONE SEAT

20741

REF. GB/T 9065.5

20742

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S2	
20741-14-04Z	-	M14X1.5	6	04		40.6	10.5	18.5	19
20741-16-05Z	-	M16X1.5	8	05		43.4	10	20	22
20741-18-06Z	20742-18-06Z	M18X1.5	10	06		45.7	10	21.4	24
20741-22-08Z	20742-22-08Z	M22X1.5	12	08		58.9	10	24	27
20741-27-10Z	20742-27-10Z	M27X1.5	16	10		70.7	11	26.4	32
20741-30-12Z	20742-30-12Z	M30X1.5	20	12		77.4	11	30	36
20741-33-12Z	20742-33-12Z	M33X2	20	12		78.1	13	30	41
20741-33-16Z	20742-33-16Z	M33X2	25	16		87.7	13	32.3	41
20741-36-16Z	20742-36-16Z	M36X2	25	16		85.7	14	31.5	41
20741-39-16Z	20742-39-16Z	M39X2	25	16		87	14	31.8	46
20741-45-20WZ	20742N-45-20WZ	M45X2	32	20		100.2/102.8	15	39.4	50
20741-52-24WZ	20742N-52-24WZ	M52X2	40	24		115.3/118.3	17	40.9	60

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/WZ	20741-22-08Z
304 stainless steel	SR/SRW	20741-22-08SR
316L stainless steel	SV/SVW	20741-22-08SV
316Ti stainless steel	SY/SYW	20741-22-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	20741-22-08Z	96	360
Durakote plating	ZD	20741-22-08ZD	360	720
Zinc-nickel plating	ZN	20741-22-08ZN	1000	-