


HOSE FITTING



22691K
22692K

90° BSP COMPACT FEMALE 60°
CONE

REF. ISO 12151-6

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS				
BRAIDED	SPIRAL		DN	DASH	A	C	H	S1	S2
22691K-04-04Z	-	G1/4"X19	6	04	17.5	5.5	18.5	11	19
22691K-06-04Z	-	G3/8"X19	6	04	20	6.3	24	16	22
22691K-06-05Z	-	G3/8"X19	8	05	20	6.3	24	16	22
22691K-06-06Z	22692K-06-06Z	G3/8"X19	10	06	20	6.3	24	16	22
22691K-08-06Z	22692K-08-06Z	G1/2"X14	10	06	23	7.5	28.5	19	27
22691K-08-08Z	22692K-08-08Z	G1/2"X14	12	08	23.5	7.5	28.5	19	27
22691K-10-10Z	22692K-10-10Z	G5/8"X14	16	10	24.5	9.5	30.5	22	30
22691K-12-12Z	22692K-12-12Z	G3/4"X14	20	12	27.5	10.9	33	27	32
22691K-16-16Z	22692K-16-16Z	G1"X11	25	16	43	11.7	38.5	33	41

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	22691K-08-08Z
304 stainless steel	SR	22691K-08-08SR
316L stainless steel	SV	22691K-08-08SV
316Ti stainless steel	SY	22691K-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	22691K-08-08Z	96	360
Durakote plating	ZD	22691K-08-08ZD	360	720
Zinc-nickel plating	ZN	22691K-08-08ZN	1000	-