



HOSE FITTING



28611
28612



28611-W
28612-W

JIS METRIC FEMALE 60° CONE SEAT

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S1	S2
28611-12-04Z	-	M12X1.5	6	04		20	9	17	17
28611-14-04WZ	-	M14X1.5	6	04		23	10.5	17	19
28611-14-06Z	28612-14-06Z	M14X1.5	10	06		21	10.5	19	19
28611-16-04Z	-	M16X1.5	6	04		24	10	22	22
28611-16-05Z	-	M16X1.5	8	05		24	10	22	22
28611-16-06Z	28612-16-06Z	M16X1.5	10	06		24	10	22	22
28611-18-06Z	28612-18-06Z	M18X1.5	10	06		24	11.5	24	24
28611-18-08Z	28612-18-08Z	M18X1.5	12	08		24.5	11.5	24	24
28611-20-08Z	28612-20-08Z	M20X1.5	12	08		28.5	12	27	27
28611-22-08Z	28612-22-08Z	M22X1.5	12	08		25.5	14	27	27
28611-24-08Z	28612-24-08Z	M24X1.5	12	08		27.5	15	32	32
28611-24-10Z	28612-24-10Z	M24X1.5	16	10		28	15	32	32
28611-30-12Z	28612-30-12Z	M30X1.5	20	12		28.5	18.3	36	36
28611-33-12Z	28612-33-12Z	M33X1.5	20	12		31	21.3	41	41
28611-33-16Z	28612-33-16Z	M33X1.5	25	16		32	21.3	41	41
28611-36-20Z	28612N-36-20Z	M36X1.5	32	20		35.5/38.1	20	46	46
28611-42-24WZ	28612N-42-24WZ	M42X1.5	40	24		40/43	18.8	55	55

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/WZ	28611-22-08Z
304 stainless steel	SR/SRW	28611-22-08SR
316L stainless steel	SV/SVW	28611-22-08SV
316Ti stainless steel	SY/SYW	28611-22-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	28611-22-08Z	96	360
Durakote plating	ZD	28611-22-08ZD	360	720
Zinc-nickel plating	ZN	28611-22-08ZN	1000	-